



WHAT IT'S FOR

- ✓ Back sealer: Water-based water-repellent protector against salts and other contaminants.



MATERIALS

- TERRACOTTA
- UNPOLISHED LIMESTONE AND SANDSTONE
- CRYSTALLINE MARBLE AND POLISHED LIMESTONE
- AGGLOMERATES, MARBLE AND CONCRETE



ADVANTAGES

- Non-film forming penetrating product.
- Breathable (EN ISO7783-2).
- UV resistant (ASTM G154).
- Does not yellow.
- Does not alter the material's appearance.
- Does not alter the skid resistance of the surface (UNI EN ISO 10545 - 17).
- Suitable for outdoor use.
- Solvent free.
- Consolidating.



HOW TO USE IT

5-SIDE PROTECTION (BACK AND 4 SIDES): to block contaminants (stains, yellow stains, glue errors when laying) from the back and 4 sides of the material.

IN-LINE: FT 909 can be applied after the polishing line using the following methods: roller, airless, drip method followed by brushing, a combination of the above methods.

MANUALLY: FT 909 can be applied after the polishing line using the following methods: roller, airless, paintbrush

6-SIDE PROTECTION: to block contaminants (stains, yellow stains, glue errors when laying) from the back and 4 sides of the material and to also create a waterproof effect on the front.

IN-LINE: FT 909 can be applied after the polishing line using the following methods: airless or dipping.

MANUALLY: dip the material in FILA FT 909 for a few seconds, take out and immediately remove any residues of product from all 6 sides.

Attention: Regardless of the application method, any residues of the product must be thoroughly removed from the surface.



OPERATORS & SYSTEMS

Contains no hydrocarbon solvents so no aspiration system is required for the plant.

No PPE necessary (Personal Protective Equipment).

Composizione: Single-component system of water-dispersed organic and silicon compounds.

Shelf life: 2 years for sealed product stored indoors at a temperature of 20°C.

Confezioni: 100 litre cans. 1.000 litre cubes.

Chemical-physical characteristics



- Appearance: clear liquid
- Colour: colourless
- Odour: pungent
- Density: 1.014kg/l
- Flash point: >61°C
- Storage temperature: 5°C to 30°C.
- Must be applied to material at temperatures between 10° and 30°C.
- Maximum temperature of the surface to be treated: 40°C.

Safety warnings

Warning. Danger. Hazard statements: causes severe skin burns and eye damage. Precautionary statements: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Wear protective gloves / protective clothing / eye protection / face protection.

