



WHAT IT'S FOR

- ✓ Protects and enhances the colour of outdoor surfaces in concrete, by impregnation.
- ✓ Gives the material a resistant glossy finish and stain protection.



MATERIALS

- ROUGH-FINISH CONCRETE
- SELF-BLOCKING PAVING
- MARBLE CHIP TILES FOR OUTDOOR USE



ADVANTAGES

- Protects the treated material during handling at the factory.
- Protects the material before and during installation.
- Makes cleaning after installation easier, allowing neutral detergents to be used.
- Prevents the accumulation of dirt on the surface.
- Makes maintenance simpler.
- Preserves breathability.
- Penetrating product.
- Water repellent¹ with stain protection effect.
- Reduces tendency to dirty.
- Colour-enhancing.
- UV resistant (ASTM G154).
- Does not yellow or flake.
- Makes the material more resistant to the elements.
- Consolidates the surface, for an anti-dust effect.

¹ DIN 52617: 1979 Capillary absorption measured on limestone surface: surface absorption goes from 9% on untreated to 0.8% on treated material.

Composizione: Blend of organic resins.



HOW TO USE IT

Dilution. The product does not need diluting, it is ready for use.

Application. First, send the material through a conveyor dryer to remove polishing water and any residues from the surface. Apply **FILAFT1226** using the airless method, spreading evenly over the entire surface with a rotating soft-bristle brush. Remove any excess product with one or two rotating brushes.

How much to use. Product coverage will depend on the type of material, application method and temperature of the material when the product is applied.

Protection after installation. Initial cleaning: **FILACLEANER**.

Warning: At the end of the work session, flush the system with running water.

Shelf life: 2 years for sealed product stored indoors at a temperature of 20°C.



OPERATORS & SYSTEMS

Contains no hydrocarbon solvents so no aspiration system is required.

Technically odourless, does not contain hydrocarbon solvents.

No PPE necessary (Personal Protective Equipment).

We recommend gloves be worn when handling the product.

Confezioni: 100 litre cans. 1.000 litre cubes.

Chemical-physical characteristics



- Appearance: milky white liquid
- Odour: typical of resin
- Density: 1.024 kg/l
- Storage temperature: 5° to 30° C
- Application temperature: 5° to 30°C
- Maximum temperature of the surface: 50°C

Safety warnings

