

FILAFT PROLUX

POLISH FOR SLABS OF MARBLE AND GRANITE



WHAT IT'S FOR

- ✓ It polishes and enhances slabs of marble and granite.



MATERIALS

- LIMESTONE, MARBLE, TRAVERTINE
- CONCRETE AND MARBLE AGGLOMERATES
- MARBLE AGGLOMERATES



ADVANTAGES

- Non-film forming penetrating product.
- UV resistant (ASTM G154).
- Does not yellow.
- Suitable for indoors and out.
- Breathable (EN ISO7783-2).



HOW TO USE IT

Dilution. The product does not need diluting as it is ready for use.
Application. To enhance the slabs: after polishing, first send the material through a conveyor dryer to remove polishing water and any residues from the surface. Apply FILAFT PROLUX using roller, drip or airless method, spreading evenly over the entire surface with a rotating soft-bristle brush. Remove any excess product with one or two rotating brushes. **How much to use.** Product coverage will depend on the type of material, application method and temperature of the material when the product is applied. **Operations after installation.** Initial cleaning: FILACLEANER or FILAPS87. Protectors: FILAFOB for a natural effect, FILASTONE PLUS for a colour-enhancing effect.

Warning: After stopping work for the day, clean the system with white spirits or any other kind of petroleum spirits.



OPERATORS & SYSTEMS

The product has a solvent base so extractors should be installed if not already present over the application area and/or the room should be aired during application.

Composition: Dispersion of organic resins in hydrocarbon solvent.

Shelf life: 5 years for sealed product stored indoors at a temperature of 20°C.

Sizes: 5 litre cans.

Chemical-physical characteristics



- Appearance: clear liquid
- Colour: colourless
- Odour: slight solvent odour
- Density: 0.775 kg/l
- Flash point: 40°C
- Storage temperature: 0° to 30° C
- Application temperature: 5° to 30°C
- Maximum temperature of the surface to be treated: 40°C

Safety warnings

Avvertenze. Danger - Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. Precautionary statements: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Wear protective gloves / eye protection / face protection. IF INHALED: remove person to fresh air and keep comfortable for breathing. In case of fire: use ... to extinguish. Contains: De-aromatized mineral turpentine.

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and checks. Fila accepts no liability for improper use of its product.

